POLARIS SPORTSMAN 850 SPORTSMAN 850 XP (2011-2011)



| ENGINE EHO850LE Capacity: 1,9 liter | | | | |
|--|--|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| Expulsa RR 5W-50 | | | | |
| Change every 1000 miles/ 100 hours/ 6 months | | | | |
| USE | | CLIMATE | | |
| Initial service | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| Expulsa RR 5W-50 | | | | |
| Change every 500 miles/ 1 months/ 20 hours | | | | |

DIFFERENTIAL FRONT Capacity: 0,28 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

| DIFFERENTIAL REAR Capacity: 0,21 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 1000 miles/ 12 months/ 100 hours

TRANSMISSION CVT 1

Capacity: 0,95 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM ACTIVE DESCENT CONTROL (ADC) Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.) | | | | |
|--|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | | |
| | | | | |

Change every 2000 miles/24 months/200 hours

POLARIS SPORTSMAN 850 SPORTSMAN 850 XP (2011-2011)



| COOLING SYSTEM Capacity: 1,9 liter | | | |
|---------------------------------------|--|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| Coolant SP 11 | | | |
| Change avery 24 menths/200 hours | | | |

Change every 24 months/ 200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.