

RIEJU PACIFIC PACIFIC 50 (2007-2010)**ENGINE**

Capacity: 0,85 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS

Capacity: 0,11 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-4 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90**

Change every 10000 km/ 12 months

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-4 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90**

Change every 1000 km

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4**

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.