

SKI-DOO EXPEDITION EXPEDITION LE 900 ACE (2015-2016)



ENGINE Rotax 903
Capacity: 3,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Check every 500 km/ 10 hours, change every 6000 km/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Change every 500 km/ 10 hours

USE	CLIMATE
Second change only	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Change every 3000 km/ 12 months

GEARBOX 2/1
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Check every 1500 km, change every 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 500 km/ 10 hours

SKI-DOO EXPEDITION EXPEDITION LE 900 ACE (2015-2016)



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 12 months, change every 6000 km/ 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 500 km/ 10 hours

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 60 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 500 km/ 10 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.