

# SKI-DOO EXPEDITION EXPEDITION SE 600

## H.O. E-TEC (2014-2014)

**ENGINE + AUTOMATIC LUBRICATION** Rotax 593

Capacity: 2,9 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**GEARBOX** 2/1

Capacity: 0,7 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

Check every 1500 km, change every 12 months

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

Change every 500 km/ 10 hours

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

Check every 12 months, change every 6000 km/ 24 months

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

Check every 500 km/ 10 hours

# SKI-DOO EXPEDITION EXPEDITION SE 600

## H.O. E-TEC (2014-2014)

**COOLING SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Change every 60 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 500 km/ 10 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*