SKI-DOO SKANDIC SKANDIC WT 600 ACE (2012-2013)



ENGINE Rotax 602 Capacity: 2,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Helar 0W-40	
Change every 6000 km/ 12 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Helar 0W-40	
Change every 500 km/ 10 hours	

GEARBOX 2/1 Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
01 1 1 100	

Check every 1500 km, change every 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 6000 km/ 24 months

Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Initial service		Moderate	
USE		CLIMATE	

Check every 500 km/ 10 hours

SKI-DOO SKANDIC SKANDIC WT 600 ACE (2012-2013)



Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Initial service		Moderate
USE		CLIMATE
Change every 60 months		
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.