

# SUZUKI AN/UH BURGMAN AN 400

## BURGMAN (2003-2006)

**ENGINE**

Capacity: 2,3 liter (Dry fill), Capacity: 2 liter (Service fill), Filter capacity: 0,1 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

## PRODUCT RECOMMENDATION 2

**Expulsa RR 15W-50**

## PRODUCT RECOMMENDATION 3

**Expulsa RR 10W-40***Change every 6000 km/ 6 months*

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

## PRODUCT RECOMMENDATION 2

**Expulsa RR 15W-50**

## PRODUCT RECOMMENDATION 3

**Expulsa RR 10W-40***Change every 1000 km/ 1 months***FINAL REDUCTION**

Capacity: 0,19 liter, Capacity: 0,2 liter (Overhaul capacity)

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 12000 km/ 12 months*

## USE

Normal

## CLIMATE

Arctic

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**SP Gear 1071***Change every 12000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Check every 6000 km/ 6 months, change every 24 months*

# SUZUKI AN/UH BURGMAN AN 400

## BURGMAN (2003-2006)



### COOLING SYSTEM

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

#### PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

Check every 12000 km/ 12 months, change every 24 months

### FRONT FORK

Capacity: 284 CM3 (each)

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*