## SUZUKI AN/UH BURGMAN AN 650 BURGMAN (2002-2004)



ENGINE Capacity: 2,9 liter, Capacity: 3,4 liter (Overhaul capacity), Filter capacity: 0,3 liter				
use Normal		CLIMATE		
		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		
Change every 6000 km/ 6 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		
Change every 1000 km				

FINAL REDUCTION Capacity: 0,3 liter, Capacity: 0,43 liter	er (Overhaul capacity)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 12000 km/ 12 months	·	·

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 6000 km/ 12 months, cha	nge every 24 months	

COOLING SYSTEM Capacity: 1,3-1,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	<u>'</u>

## FRONT FORK Capacity: 0,46-0,48 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## SUZUKI AN/UH BURGMAN AN 650 BURGMAN (2002-2004)



WET CLUTCH Capacity: 0,36 liter, Capacity: 0,4 liter (Overhaul capacity)				
use Normal		climate Moderate		
			PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		
Charles are 6000 less / 42 magniths	abanana ayan dagaaa kara / 2.4 maantha	·		

Check every 6000 km/12 months, change every 12000 km/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.