

# SUZUKI AN/UH BURGMAN UH 200

## BURGMAN (2007-2013)

**ENGINE**

Capacity: 1,5 liter (Dry fill), Capacity: 1,3 liter (Service fill), Filter capacity: 0,1 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 5000 km/ 15 months*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

## PRODUCT RECOMMENDATION 2

**Expulsa RR 15W-50**

## PRODUCT RECOMMENDATION 3

**Expulsa RR 5W-40***Change every 5000 km/ 15 months*

## USE

Initial service

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 1000 km/ 3 months*

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

## PRODUCT RECOMMENDATION 2

**Expulsa RR 15W-50**

## PRODUCT RECOMMENDATION 3

**Expulsa RR 5W-40***Change every 1000 km/ 3 months***FINAL REDUCTION**

Capacity: 0,15 liter, Capacity: 0,16 liter (Dry fill)

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Check every 10000 km/ 30 months*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

## PRODUCT RECOMMENDATION 2

**Expulsa RR 15W-50**

## PRODUCT RECOMMENDATION 3

**Expulsa RR 5W-40***Check every 10000 km/ 30 months*

# SUZUKI AN/UH BURGMAN UH 200

## BURGMAN (2007-2013)



### HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Check every 5000 km/ 15 months, change every 24 months*

### COOLING SYSTEM

Capacity: 1,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Change every 24 months*

### FRONT FORK

Capacity: 141 CM3 (each)

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*