

# SUZUKI DL V-STROM DL650A V-STROM

## (2012-2016)



### ENGINE/TRANSMISSION

Capacity: 3 liter (Dry fill), Capacity: 2,75 liter (Service fill), Filter capacity: 0,35 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 12000 km/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

PRODUCT RECOMMENDATION 2

**Expulsa RR 15W-50**

PRODUCT RECOMMENDATION 3

**Expulsa RR 5W-40***Change every 12000 km/ 12 months*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 1000 km/ 2 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

PRODUCT RECOMMENDATION 2

**Expulsa RR 15W-50**

PRODUCT RECOMMENDATION 3

**Expulsa RR 5W-40***Change every 1000 km/ 2 months*

### HYDRAULIC BRAKE SYSTEM

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Check every 6000 km/ 12 months, change every 24 months*

# SUZUKI DL V-STROM DL650A V-STROM

## (2012-2016)



### COOLING SYSTEM

Capacity: 1,95 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Coolant SP 14+</b>    |  |  |

*Change every 24000 km/ 48 months*

| USE                  | CLIMATE  |
|----------------------|----------|
| Normal (alternative) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2      |  |
|--------------------------|-------------------------------|--|
| <b>Coolant SP 14+</b>    | <b>Coolant -38 Organic NF</b> |  |

*Change every 12000 km/ 24 months*

| USE                      | CLIMATE  |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

| PRODUCT RECOMMENDATION 1      |  |  |
|-------------------------------|--|--|
| <b>Coolant -38 Organic NF</b> |  |  |

*Change every 12000 km/ 24 months*

### FRONT FORK

Capacity: 530 CM3 (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*