PRODUCT RECOMMENDATION SUZUKI GS GS1000GX (1980-1981)



ENGINE/TRANSMISSION Capacity: 3,7 liter (Dry fill), Capacity: 3,3 lit	er (Service fill), Filter capacity: 0,3 liter	
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
HDX 40		
Change every 6000 km/ 12 months		-
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	HDX 20W-50	HDX 30
Change every 6000 km/ 12 months		-
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 10W-40	Expulsa 10W-40
Change every 6000 km/ 12 months		
USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
HDX 40		
Change every 1000 km/ 2 months		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	HDX 20W-50	HDX 30
Change every 1000 km/ 2 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 10W-40	Expulsa 10W-40
Change every 1000 km/ 2 months		

SUZUKI GS GS1000GX (1980-1981)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3		

Change every 24 months

FRONT FORK Capacity: 245 CM3 (each leg)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Check every 12000 km/ 24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.