

SUZUKI GSX-R GSX-R 1100 LC (1993-1997)**ENGINE/TRANSMISSION**

Capacity: 3,3 liter (Service fill), Filter capacity: 0,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-50****PRODUCT RECOMMENDATION 2****Expulsa RR 10W-40****PRODUCT RECOMMENDATION 3****Expulsa 10W-40***Change every 6000 km/ 12 months***HYDRAULIC BRAKE SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Change every 24 months***COOLING SYSTEM**

Capacity: 2,45 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF***Change every 24 months***FRONT FORK**

Capacity: 0,43 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Fork Oil RR 5***Check every 12000 km/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.