SUZUKI GT GT750 L/M/A/B (1973-1977)



ENGINE + AUTOMATIC LUBRICATION Capacity: 1,8 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Tornado	Scoosynth	2T Super		

TRANSMISSION 5 Capacity: 2,5 liter (Dry fill), Capacity: 2,2 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50		
Change every 3000 km				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50		
Change every 1000 km				

HYDRAULIC BRAKE SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-S DOT 4	Drauliquid DOT 3			
Change every 10000 km/ 12 month	78	1		

COOLING SYSTEM Capacity: 4,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 35000 km/24 months	,	

SUZUKI GT GT750 L/M/A/B (1973-1977)



FRONT FORK Capacity: 160 CM3 (each leg)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Fork Oil RR 10	
Change every 10000 km	•

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.