SUZUKI RM(-Z) RM 125 (2006-2008)



ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Tornado	Scoosynth	Maestrol

TRANSMISSION 6 Capacity: 0,8 liter (Dry fill), Capacity: 0,75 liter (Service fill)					
use Normal		climate Moderate			
				PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Expulsa RR 5W-40	Expulsa RR 10W-40	Expulsa 10W-40			
Change every 3 races/ 6 hours	-	<u> </u>			

Change every 3 races/ 6 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 1 race/2 hours, change every 12 months

COOLING SYSTEM Capacity: 1,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant -38 Organic NF			
Check every 1 race/ 2 hours, change every 12 months			

FRONT FORK

Capacity: 180 CM3 (Inner tube), Capacity: 357 CM3 (Outer tube)

We are unable to give a standard recommendation for this component. Please contact our service department.

SHOCK ABSORBER REAR

Capacity: 380 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.