

**SUZUKI RM(-Z) RM 80 (1996-2001)****ENGINE**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Tornado**

## PRODUCT RECOMMENDATION 2

**Scoosynth**

## PRODUCT RECOMMENDATION 3

**Maestrol****TRANSMISSION 6**

Capacity: 0,55 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

## PRODUCT RECOMMENDATION 2

**Expulsa 10W-40**

## PRODUCT RECOMMENDATION 3

**HDX 10W-40****HYDRAULIC BRAKE SYSTEM**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 12 months***COOLING SYSTEM**

Capacity: 0,55 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Change every 12 months***FRONT FORK**

Capacity: 0,36 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Fork Oil RR 10**

**SUZUKI RM(-Z) RM 80 (1996-2001)****SHOCK ABSORBER REAR**

Capacity: 0,15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Fork Oil RR 10</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*