

# SYM GTS LM GTS 125I LN12W1-6 (2012-2021)



## ENGINE

Capacity: 1 liter (Dry fill), Capacity: 0,8 liter (Service fill)

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40***Check every 1000 km, change every 5000 km*

### USE

Initial service

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40***Change every 1000 km*

## FINAL GEAR

Capacity: 0,11 liter (Dry fill), Capacity: 0,1 liter (Service fill)

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140***Change every 10000 km*

### USE

Normal

### CLIMATE

Arctic

### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

### PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 10000 km*

### USE

Initial service

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140***Change every 1000 km*

### USE

Initial service

### CLIMATE

Arctic

### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

### PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 1000 km*

**SYM GTS LM GTS 125I LN12W1-6 (2012-2021)****HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3**

Check every 1000 km/ 1 months, change every 20000 km/ 24 months

**COOLING SYSTEM**

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26**

Check every 5000 km/ 3 months, change every 15000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.