

SYM MAXSYM MAXSYM 400I ABS (2012-2019)

**ENGINE LX40A2-6**

Capacity: 2 liter (Dry fill), Capacity: 1,9 liter (Service fill), Filter capacity: 0,1 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Expulsa RR 10W-40****PRODUCT RECOMMENDATION 2****Expulsa 10W-40***Check every 1000 km/ 1 months, change every 5000 km/ 3 months***USE**

Initial service

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Expulsa RR 10W-40****PRODUCT RECOMMENDATION 2****Expulsa 10W-40***Change every 1000 km/ 1 months***FINAL GEAR**

Capacity: 0,35 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 85W-140***Change every 10000 km/ 6 months***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 85W-140***Change every 1000 km/ 1 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid DOT 3***Change every 30000 km/ 24 months*

SYM MAXSYM MAXSYM 400I ABS (2012-2019)



COOLING SYSTEM

Capacity: 0,45 liter (Expansion tank), Capacity: 0,65 liter (Radiator)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 15000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.