

**TM RACING END 530 END (2006-2014)****ENGINE/TRANSMISSION**

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 5W-50</b>	<b>Expulsa 10W-40</b>

*Change every 30 hours/ 150 liter consumed fuel*

USE	CLIMATE
Competition	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 5W-50</b>	<b>Expulsa 10W-40</b>

*Change every 1 each race*

USE	CLIMATE
Competition, first service only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 5W-50</b>	<b>Expulsa 10W-40</b>

*Change every 2 hours/ 12 liter consumed fuel*

USE	CLIMATE
Normal, first service only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 5W-50</b>	<b>Expulsa 10W-40</b>

*Change every 3 hours/ 15 liter consumed fuel***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>

*Change every 12 months*

USE	CLIMATE
Competition	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>

*Change every 3 races*

**HYDRAULIC CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Change every 12 months*

USE		CLIMATE
Competition		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Change every 3 races*

**COOLING SYSTEM**

Capacity: 1-1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

**FRONT FORK Kayaba**

Capacity: 0,31-0,34 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**FRONT FORK Marzocchi**

Capacity: 0,3-0,33 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Fork Oil RR 5</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*