

TM RACING MX 450FI MX (2014-2017)**ENGINE/TRANSMISSION**

Capacity: 1,5 liter (Dry fill), Capacity: 1,4 liter (Service fill)

USE	CLIMATE
Competition	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 10 hours/ 1 race*

USE	CLIMATE
Competition, first service only	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 1 hours***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Competition	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 10 hours/ 1 race, change every 12 months***HYDRAULIC CLUTCH SYSTEM**

USE	CLIMATE
Competition	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 10 hours/ 1 race, change every 12 months***COOLING SYSTEM**

Capacity: 1,3 liter

USE	CLIMATE
Competition	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Check every 10 hours/ 1 race***FRONT FORK** Kayaba

Capacity: 0,33-0,36 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TM RACING MX 450FI MX (2014-2017)**FRONT FORK** Marzocchi

Capacity: 0,32-0,36 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 5		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.