PRODUCT RECOMMENDATION

TM RACING SMX 450 SMX (2006-2014)

ENGINE/TRANSMISSION
Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 5W-50	**Expulsa 10W-40**	

Change every 30 hours/ 150 liter consumed fuel

USE	CLIMATE
Competition	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 5W-50	**Expulsa 10W-40**	

Change every 1 each race

USE	CLIMATE
Competition, first service only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 5W-50	**Expulsa 10W-40**	

Change every 2 hours/ 12 liter consumed fuel

USE	CLIMATE
Normal, first service only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 5W-50	**Expulsa 10W-40**	

Change every 3 hours/ 15 liter consumed fuel

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Change every 12 months

USE	CLIMATE
Competition	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Change every 3 races

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TM RACING SMX 450 SMX (2006-2014)

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Change every 12 months

USE		CLIMATE
Competition		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Change every 3 races

COOLING SYSTEM
Capacity: 1-1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant -38 Organic NF	**Coolant -26**	

FRONT FORK Marzocchi
Capacity: 0,27-0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 5		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367