

TRIUMPH ROCKET III ROCKET III TOURING

(2008-2014)



ENGINE/TRANSMISSION

Capacity: 5,4 liter, Capacity: 5,9 liter (Dry fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	Expulsa RR 5W-40	Expulsa RR 10W-40

Change every 16000 km/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	Expulsa RR 5W-40	Expulsa RR 10W-40

Change every 800 km/ 1 months

FINAL DRIVES

Capacity: 0,17 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Gearlube HS GL-5 75W-90	Syngear 75W-90

Check every 16000 km/ 12 months, change every 32000 km/ 24 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Gearlube HS GL-5 75W-90	Syngear 75W-90

Check every 800 km/ 1 months

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 16000 km/ 12 months, change every 24 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 800 km/ 1 months

TRIUMPH ROCKET III ROCKET III TOURING

(2008-2014)



COOLING SYSTEM

Capacity: 3,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO*Check every 16000 km/ 12 months, change every 32000 km/ 24 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO*Check every 800 km/ 1 months*

FRONT FORK

Capacity: 649 CM3 (each side)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Fork Oil RR 10*Check every 16000 km/ 12 months, change every 64000 km/ 48 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Fork Oil RR 10*Check every 800 km/ 1 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.