

TRIUMPH THUNDERBIRD THUNDERBIRD COMMANDER 1700 (2013-2020)

**ENGINE/TRANSMISSION**

Capacity: 4,8 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 5W-40	Expulsa RR 10W-40

Check every 3000 km, change every 10000 km/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 5W-40	Expulsa RR 10W-40

*Change every 800 km/ 1 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Change every 24 months***GREASE POINTS/NIPPLES GENERAL**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	Q5 MP Calcep Grease EP 2

COOLING SYSTEM OEM GREEN FLUID

Capacity: 2,55 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Change every 20000 km/ 24 months

TRIUMPH THUNDERBIRD THUNDERBIRD COMMANDER 1700 (2013-2020)



COOLING SYSTEM OEM ORANGE FLUID

Capacity: 2,55 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 20000 km/ 24 months

FRONT FORK

Capacity: 677 CM3 (each leg)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 10		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.