

URAL ADIRONDAC ADIRONDAC (2000-2003)**ENGINE**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 15W-50****PRODUCT RECOMMENDATION 2****HDX 20W-50****SHAFT DRIVE**

Capacity: 105 CM3

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90****TRANSMISSION 4/1**

Capacity: 1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 15W-50****PRODUCT RECOMMENDATION 2****HDX 20W-50****HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4****PRODUCT RECOMMENDATION 3****Drauliquid DOT 3****SHOCK ABSORBER REAR**

Capacity: 105 CM3 (each side)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Fork Oil RR 10****PRODUCT RECOMMENDATION 2****Fork Oil RR 5**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.