

# URAL GEAR UP GEAR UP (2014-2015)



## ENGINE

Capacity: 2,1 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 15W-50</b>	<b>Bi-Turbo 20W-50</b>

*Change every 5000 km/ 12 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
<b>Expulsa RR 5W-40</b>	

*Change every 5000 km/ 12 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 15W-50</b>	<b>Bi-Turbo 20W-50</b>

*Change every 1000 km*

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1	
<b>Expulsa RR 5W-40</b>	

*Change every 1000 km*

## SHAFT DRIVE

Capacity: 135 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Check every 5000 km, change every 10000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Change every 1000 km*

# URAL GEAR UP GEAR UP (2014-2015)



## TRANSMISSION 4/1

Capacity: 0,9 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Expulsa RR 15W-50</b>	<b>Bi-Turbo 20W-50</b>	

Check every 5000 km, change every 10000 km

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
<b>Expulsa RR 5W-40</b>		

Check every 5000 km, change every 10000 km

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Expulsa RR 15W-50</b>	<b>Bi-Turbo 20W-50</b>	

Change every 1000 km

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
<b>Expulsa RR 5W-40</b>		

Change every 1000 km

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

Check every 5000 km, change every 30000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.