VESPA LX(V) LX 125 4T 3V (2012-2017)



ENGINE M687M Capacity: 1,22 liter (Service fill), Filter capacity: 0,12 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-40				
Check every 2500 km, change every 10000 km				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
Eventee DD EW 40				
Expulsa RR 5W-40				

HUB REDUCTIONS REAR Capacity: 200 CM3		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 10000 km	'	

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Charle ayon, 5000 km, abanga ayon, 2	14 months		

Check every 5000 km, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.