## VESPA LX(V) LX 150 4T EURO 3 (2007-2016)



ENGINE Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Check every 3000 km, change every 6000	) km	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 1000 km		
HUB REDUCTIONS REAR		
Capacity: 0,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

Check every 6000 km, change every 24000 km				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90			

Unigear HS GL-3/GL-5 80W-90

Change every 1000 km

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Check every 6000 km, change every 24 months				

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 1000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

## PRODUCT RECOMMENDATION

## VESPA LX(V) LX 150 4T EURO 3 (2007-2016)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.