

# VMOTO SCARTT II SCARTT II 500 (2011-2011)



## ENGINE

Capacity: 1,9 liter (Service fill), Filter capacity: 0,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 10W-40</b>	<b>HDX 15W-40</b>

Check every 250 km/ 1 months/ 25 hours/ Daily, change every 1000 km/ 6 months/ 100 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 10W-40</b>	<b>HDX 15W-40</b>

Change every 250 km/ 3 months/ 20 hours

## DIFFERENTIAL FRONT

Capacity: 330 CM3 (Dry fill), Capacity: 280 CM3 (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

Check every 250 km/ 1 months/ 25 hours, change every 12 months

## DIFFERENTIAL REAR

Capacity: 300 CM3 (Dry fill), Capacity: 250 CM3 (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

Check every 250 km/ 1 months/ 25 hours, change every 12 months

## HYDRAULIC BRAKE SYSTEM

Capacity: 100 CM3 (Reservoir)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

Check every 2000 km/ 24 months/ 200 hours, change every 24 months

# VMOTO SCARTT II SCARTT II 500 (2011-2011)

**COOLING SYSTEM**

Capacity: 1,9 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Check every Daily, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*