

YAMAHA (USA) FJR FJR 1300 (2005-2008)**ENGINE/TRANSMISSION**

Capacity: 4 liter, Filter capacity: 0,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

FINAL DRIVES

Capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011*Change every 16000 miles/ 24 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011*Change every 600 miles/ 1 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 24 months***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 24 months***COOLING SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF*Change every 16000 miles/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

YAMAHA (USA) FJR FJR 1300 (2005-2008)



inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.