

**YAMAHA (USA) WR WR 250 F (2011-2014)****ENGINE/TRANSMISSION**

Capacity: 1,4 liter (Dry fill), Capacity: 1,1 liter (Service fill), Filter capacity: 0,1 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Expulsa RR 5W-50</b>  | <b>Expulsa RR 15W-50</b> | <b>Expulsa RR 10W-40</b> |

*Change every 1800 miles/ 3 months*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Expulsa RR 5W-50</b>  | <b>Expulsa RR 15W-50</b> | <b>Expulsa RR 10W-40</b> |

*Change every 600 miles/ 1 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |  |
|----------------------------------|---------------------------|--|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |  |

*Check every 1200 miles/ 3 months, change every 12 months***COOLING SYSTEM**

Capacity: 1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      |  |  |
|-------------------------------|--|--|
| <b>Coolant -38 Organic NF</b> |  |  |

*Check every 1200 miles/ 3 months, change every 12 months***FRONT FORK**

Capacity: 132 mm (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.