PRODUCT RECOMMENDATION

YAMAHA (USA) XV VIRAGO XV 1100 VIRAGO (1998-1999)

ENGINE/TRANSMISSION
Capacity: 3,6 liter (Dry fill), Capacity: 3,1 liter (Service fill), Filter capacity: 0,1 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		

Change every 4000 miles/ 6 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		

Change every 600 miles/ 1 months

FINAL DRIVES
Capacity: 0,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	**Gearlube GL-4 80W**	

Change every 16000 miles/ 24 months

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367