YAMAHA (USA) XV XV 19 STRATOLINER MIDNIGHT (2008-2009)



ENGINE/TRANSMISSION Capacity: 4,9 liter, Filter capacity: 0,8 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Expulsa RR 15W-50				
Change every 4000 miles/ 6 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
Expulsa RR 15W-50				
Change every 600 miles/ 1 months				

FINAL DRIVES Capacity: 0,55 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube GL-4 80W		
Check every 8000 miles/ 12 months, change every 16000 miles/ 24 months			

USE CLIMATE
Initial service Moderate

PRODUCT RECOMMENDATION 1
PRODUCT RECOMMENDATION 2

SP Gear 5015 Gearlube GL-4 80W

Change every 600 miles/ 1 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 24 months				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.