YAMAHA (USA) XVZ XVZ 13 ROYAL STAR **VENTURE S** (2010-2013)



ENGINE/TRANSMISSION Capacity: 3,7 liter (Service fill), Filter capacity: 0,2 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		
Change every 4000 miles/ 6 months				
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		
Change every 600 miles/ 1 months				

FINAL DRIVES Capacity: 0,2 liter			
use Normal		CLIMATE	
		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube GL-4 80W		
Chack avery 8000 miles/ 12 month	s change every 16000 miles/ 24 months		

Check every 8000 miles/12 months, change every 16000 miles/24 months

SP Gear 5015	Gearlube GL-4 80W	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Initial service		Moderate
USE		CLIMATE

Change every 600 miles/ 1 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4				
Check every 4000 miles/ 6 months, change every 24 months					

PRODUCT RECOMMENDATION

YAMAHA (USA) XVZ XVZ 13 ROYAL STAR **VENTURE S** (2010-2013)



COOLING SYSTEM Capacity: 3,85 liter (+ additional reservoir), Capacity: 0,35 liter (Additional reservoir)						
USE	CLIMATE					
Normal	Moderate					
PRODUCT RECOMMENDATION 1						
Coolant -38 Organic NF						
Check every 4000 miles/ 6 months, change	every 24 months					

Check every 4000 miles/ 6 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.