

# YAMAHA (USA) YFB TIMBERWOLF YFB 250 TIMBERWOLF 4X4 (1998-2001)

**ENGINE/TRANSMISSION**

Capacity: 2,3 liter (Dry fill), Capacity: 1,75 liter (Service fill), Filter capacity: 0,1 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Expulsa 10W-40***Change every 6 months*

## USE

Normal

## CLIMATE

Arctic

## PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Change every 6 months*

## USE

Initial service

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Expulsa 10W-40***Change every 1 months*

## USE

Initial service

## CLIMATE

Arctic

## PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Change every 1 months***DIFFERENTIAL**

Capacity: 0,7 liter (Dry fill), Capacity: 0,67 liter (Service fill)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W***Change every 12 months*

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W***Change every 1 months*

# YAMAHA (USA) YFB TIMBERWOLF YFB 250 TIMBERWOLF 4X4 (1998-2001)

**FINAL GEAR**

Capacity: 0,13 liter (Dry fill), Capacity: 0,12 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>	

*Change every 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>	

*Change every 1 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*