## YAMAHA (USA) YFM GRIZZLY YFM 35 GRIZZLY 350 4X4 YFM35FGD (2013-2014)



<b>ENGINE</b> Capacity: 2,3 liter, Filter capacity: 0,1 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40
Change every 1600 miles/ 6 months/ 160 i	hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 1600 miles/ 6 months/ 160	hours	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40
Change every 200 miles/ 1 months/ 20 hou	urs	
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 200 miles/ 1 months/ 20 hou	urs	

DIFFERENTIAL REAR Capacity: 0,35 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube GL-4 80W		

Change every 3200 miles/ 12 months/ 320 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Change every 200 miles/ 1 months	/20 hours	-

Change every 200 miles/ 1 months/ 20 hours

## YAMAHA (USA) YFM GRIZZLY YFM 35 GRIZZLY 350 4X4 YFM35FGD (2013-2014)



FINAL GEAR Capacity: 0,23 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Change every 3200 miles/ 12 months/ 3.	20 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Change every 200 miles/ 1 months/ 20 h	nours	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4				
Change every 24 months	'	'			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.