YAMAHA (USA) YFM GRIZZLY YFM 45 GRIZZLY 450 4X4 YFM45FG/FGH (2007-2007)



USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40	
Change every 1600 miles/ 6 months/	160 hours		
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-40			
Change every 1600 miles/ 6 months/	160 hours		
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40	
Change every 200 miles/ 1 months/ 2	20 hours		
USE		CLIMATE	
Initial service		Arctic	
PRODUCT RECOMMENDATION 1			
Eventee DD EW 40			
Expulsa RR 5W-40			

SP Gear 5015	Gearlube GL-4 80W
Change every 3200 miles/ 12 months/ 320	hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
SP Gear 5015	Gearlube GL-4 80W	

PRODUCT RECOMMENDATION 2

Change every 200 miles/ 1 months/ 20 hours

Normal

PRODUCT RECOMMENDATION 1

Moderate

YAMAHA (USA) YFM GRIZZLY YFM 45 GRIZZLY 450 4X4 YFM45FG/FGH (2007-2007)



FINAL GEAR Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Change every 3200 miles/ 12 mont	hs/ 320 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Change every 200 miles/ 1 months/	/ 20 hours	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 24 months	,			

COOLING SYSTEM
Capacity: 1,3 liter (Radiator), Capacity: 0,25 liter (Reservoir)

USE

Normal

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149 7600 AC Almelo