PRODUCT RECOMMENDATION

YAMAHA (USA) YFM KODIAK YFM 400 KODIAK 4X4 (1998-1998)

ENGINE/TRANSMISSION

Capacity: 3,7 liter (Dry fill), Capacity: 3,1 liter (Service fill), Filter capacity: 0,1 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		

Change every 6 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		

Change every 6 months

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		

Change every 1 months

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		

Change every 1 months

DIFFERENTIAL

Capacity: 0,7 liter (Dry fill), Capacity: 0,67 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	**Gearlube GL-4 80W**	

Change every 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	**Gearlube GL-4 80W**	

Change every 1 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

YAMAHA (USA) YFM KODIAK YFM 400 KODIAK 4X4 (1998-1998)

FINAL GEAR
Capacity: 0,25 liter (Dry fill), Capacity: 0,19 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	**Gearlube GL-4 80W**	

Change every 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	**Gearlube GL-4 80W**	

Change every 1 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367