YAMAHA (USA) YFM RAPTOR YFM 35 RAPTOR (2007-2009)



ENGINE/TRANSMISSION Capacity: 2,6 liter (Service fill), Filter capacity: 0,1 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Expulsa 10W-40			
Change every 1600 miles/ 6 months/ 160 hours			
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1			
Expulsa 10W-40			
Change every 200 miles/ 1 months/ 20 hours			

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 24 months	!		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.