

YAMAHA (USA) YZ YZ 450 FF 1SL5 (2015-2019)



ENGINE/TRANSMISSION

Capacity: 0,9-0,95 liter (Dry fill), Capacity: 0,64-0,69 liter (Service fill), Filter capacity: 0,02 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50

PRODUCT RECOMMENDATION 2

Expulsa RR 15W-50

PRODUCT RECOMMENDATION 3

Expulsa RR 10W-40*Check every 3 hours/ 1 race, change every 8 hours/ 3 races*

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 12 months*

COOLING SYSTEM

Capacity: 1,03-1,04 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF*Check every 1 race, change every 24 months*

FRONT FORK

Capacity: 496-511 CM3 (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.