YAMAHA DT DT 125 LC 57U0 (1985-1985)



ENGINE + AUTOMATIC LUBRICATION Capacity: 1,2 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Tornado	Scoosynth	Maestrol		

TRANSMISSION 6 Capacity: 0,55 liter (Reservoir), Capacity: 0,63 liter (Total)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Expulsa RR 10W-40	HDX 10W-40				
Change every 24000 km					

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 24 months	·

COOLING SYSTEM Capacity: 0,13 liter (Reservoir), Capacity: 0,64 liter (Total)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Coolant -38 Organic NF				
Change every 24000 km				

FRONT FORK Capacity: 0,37 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 10		
Check every 6000 km, change every 12000 km/ 12 months		

PRODUCT RECOMMENDATION

YAMAHA DT DT 125 LC 57U0 (1985-1985)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.