

## YAMAHA DT DT 50 MX (1981-1992)

**ENGINE + AUTOMATIC LUBRICATION**

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Tornado</b>	<b>Scoosynth</b>	<b>Maestrol</b>

**TRANSMISSION 5**

Capacity: 0,65 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Expulsa RR 10W-40</b>	<b>HDX 10W-40</b>	

Change every 3000 km

**HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

Check every 3000 km, change every 24 months

**FRONT FORK**

Capacity: 0,21 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Fork Oil RR 10</b>		

Change every 6000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.