YAMAHA MT / MTT TRACER MT-07 (2013-2015)



ENGINE/TRANSMISSION Capacity: 2,6 liter (Service fill), Filte	er capacity: 0,3 liter		
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40	
Check every 12 months, change ev	very 10000 km		
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40	
O / / / / / / / / / / / / / / / / / / /		1	

Change every 1000 km

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 10000 km/ 12 months, change every 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
01 1 100001	1	

Check every 1000 km

COOLING SYSTEM Capacity: 1,6 liter (Radiator + engine), Capacity: 0,25 liter (Reservoir)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Coolant -38 Organic NF				

Check every 10000 km/ 12 months, change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.