

YAMAHA T 135 SNIPER T 135 SE SNIPER (2006-2016)



ENGINE/TRANSMISSION

Capacity: 0,9 liter (Dry fill), Capacity: 0,8 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50

Change every 6000 km/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50

Change every 1000 km

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 24 months

COOLING SYSTEM

Capacity: 0,6 liter (Dry fill), Capacity: 0,3 liter (Reservoir)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 6000 km/ 12 months, change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.