

# YAMAHA XP TMAX XP 500(A) TMAX (2007-2008)



## ENGINE

Capacity: 2,9 liter, Filter capacity: 0,1 liter

### USE

Flexible (max)

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

### PRODUCT RECOMMENDATION 2

**Expulsa 10W-40***Change every 5000 km*

### USE

Initial service

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

### PRODUCT RECOMMENDATION 2

**Expulsa 10W-40***Change every 1000 km*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

### PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Check every 10000 km/ 12 months, change every 24 months*

## COOLING SYSTEM

Capacity: 1,5 liter (Radiator), Capacity: 0,35 liter (Reservoir)

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Check every 10000 km/ 12 months, change every 36 months*

## CHAINCASE

Capacity: 0,7 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**SP Gear 5015**

### PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W***Change every 10000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.