

**YAMAHA XV XV 535 DX VIRAGO (2000-2001)****ENGINE/TRANSMISSION**

Capacity: 2,8 liter, Filter capacity: 0,2 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Expulsa RR 15W-50</b>	<b>Expulsa RR 10W-40</b>	<b>Expulsa 10W-40</b>

*Check every 3000 km, change every 10000 km/ 12 months***SHAFT DRIVE**

Capacity: 0,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>	<b>Gearlube GL-4 80W-90</b>

*Check every 10000 km/ 12 months, change every 24 months***HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Check every 10000 km/ 12 months, change every 24 months***FRONT FORK**

Capacity: 0,23 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Fork Oil RR 10</b>		

*Check every 10000 km, change every 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.