YAMAHA YBR YBR 250 (2007-2010)



ENGINE Capacity: 1,45 liter, Filter capacity:	0,1 liter	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50
Change every 10000 km/ 12 month	es .	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50
Change every 1000 km		'

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and m	ax.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Check every 10000 km/ 12 months, ch	ange every 24 months	,

FRONT FORK
Capacity: 0-0 liter (Between min and max.)

USE

Normal

PRODUCT RECOMMENDATION 1

CLIMATE

Moderate

Check every 10000 km

Fork Oil RR 10

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.