## **YAMAHA YFM BIG BEAR YFM 40 BIG BEAR 400 4X4** (2001-2002)



ENGINE/TRANSMISSION Capacity: 3,5 liter (Dry fill), Capacity: 3 liter (Service fill), Filter capacity: 0,1 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Expulsa 10W-40				
Change every 6 months				
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-40				
Change every 6 months				
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1				
Expulsa 10W-40				
Change every 1 months				
USE		CLIMATE		
Initial service		Arctic		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-40				
Change every 1 months				
DIFFERENTIAL Capacity: 0,2 liter (Dry fill), Capacity: 0,18 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Gearlube LS 80W-90				
Change every 12 months				

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1 months	·

## **YAMAHA YFM BIG BEAR YFM 40 BIG BEAR 400 4X4** (2001-2002)



FINAL GEAR Capacity: 0,25 liter (Dry fill), Capacity: 0,23 liter (Service fill)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
SP Gear 5015	Gearlube GL-4 80W				
Change every 12 months					
USE		CLIMATE			
Initial service		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
SP Gear 5015	Gearlube GL-4 80W				

Change every 1 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and ma	x.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 24 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.