YAMAHA YFM BRUIN YFM 350 BRUIN 4X4 (2004-2005)



ENGINE Capacity: 2,3 liter, Filter capacity: 0,1 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		
Change every 6 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 6 months		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		
Change every 1 months		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 1 months		
DIFFERENTIAL Capacity: 0,35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Change every 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Change every 1 months		· · · ·

YAMAHA YFM BRUIN YFM 350 BRUIN 4X4 (2004-2005)



FINAL GEAR Capacity: 0,23 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube GL-4 80W		
Change every 12 months			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube GL-4 80W		

Change every 1 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and ma	ax.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 24 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.