

# YAMAHA YFM GRIZZLY YFM GRIZZLY 450 4X4 (2007-2014)

**ENGINE**

Capacity: 2,4 liter, Filter capacity: 0,1 liter

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Expulsa RR 15W-50****PRODUCT RECOMMENDATION 2****Expulsa RR 10W-40****PRODUCT RECOMMENDATION 3****Expulsa 10W-40***Change every 2500 km/ 6 months/ 160 hours***USE**

Normal

**CLIMATE**

Arctic

**PRODUCT RECOMMENDATION 1****Expulsa RR 5W-40***Change every 2500 km/ 6 months/ 160 hours***USE**

Initial service

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Expulsa RR 15W-50****PRODUCT RECOMMENDATION 2****Expulsa RR 10W-40****PRODUCT RECOMMENDATION 3****Expulsa 10W-40***Change every 320 km/ 1 months/ 20 hours***USE**

Initial service

**CLIMATE**

Arctic

**PRODUCT RECOMMENDATION 1****Expulsa RR 5W-40***Change every 320 km/ 1 months/ 20 hours***DIFFERENTIAL REAR**

Capacity: 0,23 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**FINAL GEAR**

Capacity: 0,38-0,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Change every 24 months*

# YAMAHA YFM GRIZZLY YFM GRIZZLY 450 4X4 (2007-2014)



## COOLING SYSTEM

Capacity: 1,3 liter (Radiator), Capacity: 0,25 liter (Reservoir)

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*