YAMAHA YZ YZ 450 F (2012-2015)



ENGINE/TRANSMISSION Capacity: 1,2 liter (Dry fill), Capacity: 1 liter (Service fill), Filter capacity: 0,5 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40	

Check every 1 race, change every 5 races

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Check every 1 race, change every 24 i	months		

COOLING SYSTEM
Capacity: 1,13 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Check every 1 race, change every 24 months

FRONT FORK

Capacity: 551 CM3 (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.