

# MERCURY MARINE MERCUISER 4.3L INBOARDS 4.3 LX V6 ALPHA ONE (1996- 2006)

**ENGINE**

Capacity: 4,3 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 40***Change every 100 hours/ 12 months*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40***Change every 100 hours/ 12 months*

## USE

Normal

## CLIMATE

Cold

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 100 hours/ 12 months*

## USE

Normal

## CLIMATE

Arctic

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20***Change every 100 hours/ 12 months***FINAL DRIVES**

Capacity: 1,16 liter, Capacity: 1,89 liter (+ additional reservoir)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Atlantic Gear Oil 75W-90***Change every 100 hours/ 12 months***HYDRAULIC SYSTEM POWER TRIM/TILT**

Capacity: 0-0 liter (Between min and max.)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 2

**HDX 10W-40**

## PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40**

# MERCURY MARINE MERCUISER 4.3L INBOARDS 4.3 LX V6 ALPHA ONE (1996- 2006)

**POWER STEERING**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Almirol</b>		

**COOLING SYSTEM**

Capacity: 19 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*