

AMC JAVELIN JAVELIN 390 V8 (1969-1970)



ENGINE

Capacity: 4,7 liter, Filter capacity: 0,95 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 6400 km/ 4 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 6400 km/ 4 months*

USE

Severe

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 1600 km*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 1600 km*

DIFFERENTIAL REAR

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 5015*Check every 6400 km*

DIFFERENTIAL REAR LIMITED-SLIP Twin-Grip

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 6400 km*

AMC JAVELIN JAVELIN 390 V8 (1969-1970)

**TRANSMISSION AUTOMATIC 3/1**

Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 6400 km***TRANSMISSION MANUAL 4/1**

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Vintage Gear 90*Check every 6400 km***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 6400 km***POWER STEERING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 6400 km***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

AMC JAVELIN JAVELIN 390 V8 (1969-1970)**COOLING SYSTEM**

Capacity: 12,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 6400 km, change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.